

studio multicore PolyWIRE XLPE - n x 2 x 0.22 mm²

- ultra flexible
- XLPE insulation (cross-linked PE)
- high temperature properties
- easy and reliable soldering without shrinking

PVC

The KLOTZ PolyWIRE has been the European bestseller for years in the range of studio connection and installation cables. By the use of a specific PVC the cable is robust and still ultra-flexible and lies flat without looping when laid out or installed. The good audio performance results from generous conductor cross section together with low capacitance. Numbered pair jackets make the assembly easier and labelling dispensable. With the latest generation of this cable a conductor insulation from cross-linked polyethylene is applied to avoid shrinking during soldering.

construction

cond. construction	stranded tinned copper, 7 x 0.20 mm
cond. cross section	0.22 mm ²
insulation	XLPE, red & blue
core arrangement	2 cores twisted to a pair
pair shielding	stranded tinned copper drain wire + AL/PET foil
pair jacket	PVC, color coded in steps of 8 pairs and numbered consecutively
cable stranding	n pairs twisted in layers
outer jacket	PVC, soft, matt

electric

conductor resistance	< 85 Ω/km
capacitance	
cond./cond.	85 pF/m
cond./shield	170 pF/m
crosstalk attenuation	> 15 kHz / 100 dB
insulation resistance	> 50 GΩ x km
test voltage	
cond./cond.	1000 V
cond./shield	500 V

mechanics

min. bending radius	5x overall diameter
working temperature	-20°C / +70°C

order code	no. of pairs	outer Ø [mm]	colour	weight [kg/m]
PW02X	2	8	black	0,065
PW04X	4	9.5	black	0,105
PW06X	6	11.6	black	0.18
PW08X	8	12.5	black	0.19
PW12X	12	15	black	0.26
PW16X	16	17	black	0.35
PW20X	20	19	black	0.42
PW24X	24	21	black	0.49
PW32X	32	24	black	0,642
PW40X	40	26.5	black	0,8

technical specifications are subject to change